



BASEPLATE DETAILS		
	SPIGOT DIA.	HOLE DETAILS (45° OFF CENTRES)
F16	Ø129.95 -0.05 (Ø5.116\" -0.002\")	4 HOLES M20x25 (0.98\") DEEP ON Ø165.0 (Ø6.50\") P.C.
FA16	Ø126.87 -0.25 (Ø4.995\" -0.010\")	4 HOLES 3/4\" UNc x 25 (0.98\") DEEP ON Ø165.0 (Ø6.50\") P.C.

MAX BORE RECTANGULAR KEY		
STD	BORE	KEY
BS4235	Ø8.0	20 x 12
BS46	2.625\"	3/4\" x 1/2\"
ANSI B17.1	2.625\"	5/8\" x 5/16\"

MAX BORE SQUARE KEY		
STD	BORE	KEY
BS4235	-	-
BS46	2.500\"	5/8\" SQ
ANSI B17.1	2.500\"	5/8\" SQ

MAX ACME THREAD = 2.7/8\"

IB7AS3 BEVEL / SPUR COMBINATION GEARBOX, 6, 8, 9, 12 & 18:1 RATIO, MANUAL INPUT, F16 BASEPLATE

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com



Regina House
Ring Road
Bramley
Leeds
LS13 4ET
United Kingdom

DRAWING No	IB7AS3
ISSUE	1
DATE	20/01/03

DRAWING No	IB7AS3
ISSUE	1
DATE	20/01/03