



BASEPLATE DETAILS		
	SPIGOT DIA.	HOLE DETAILS (22.5° OFF CENTRES)
F25	#199.95 -0.05 (#7.872" -0.002")	8 HOLES M16x20 (0.79") DEEP ON #254.0 (#10.00") P.C.
FA25	#152.25 -0.05 (#5.994" -0.002")	8 HOLES 5/8"UNCx20 (0.79") DEEP ON #254.0 (#10.00") P.C.

MAX BORE RECTANGULAR KEY		
STD	BORE	KEY
BS4235	76.0	22 x 14
BS46	3.000"	3/4" x 1/2"
ANSI B17.1	3.000"	3/4" x 1/2"

MAX BORE SQUARE KEY		
STD	BORE	KEY
BS4235	-	-
BS46	2.750"	3/4"SQ
ANSI B17.1	2.750"	5/8"SQ

MAX ACME THREAD = 3.3/8"

IB9AS6 BEVEL / SPUR COMBINATION GEARBOX, 6, 8, 9, 12, 18, 24, 36 & 48:1 RATIO, MANUAL INPUT, F25 BASEPLATE

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com



**Regina House
Ring Road
Bramley
Leeds
LS13 4ET
United Kingdom**

DRAWING No

IB9AS6

ISSUE

1

DATE

20/01/03