


Suitable for 150-series insert

DESCRIPTION	
Travel Ratio	: 5° to 95° adjustment
Turns to Close	: 14.25
Weight	: 34 Kg. (75.6lb) Excl. Handwheel

MOUNTINGHOLES	
Valve connection	: F10/F12/F14/F16
MAX. bore	: $\sqrt{36}$ [1.42] or $\sqrt{44}$ [1.73]
Actuator connection	: F12/F14/F16
MAX. shaft	: $\sqrt{52}$ [2.05] or $\sqrt{74}$ [2.91]

TORQUE	
Max. Output	: 2485 Nm ( 22,000 lbf.in.)
Max. Input	: 160 Nm ( 1420 lbf.in.)
M.A.	: 15.4 ± 15%




**rotork gears**

Nijverheidstraat 25  
7135 JZ  
The Netherlands

# GEARBOX ILG/D 1500

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTERESTS OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS.



Drawn : N.M  
Date : 05-06-06  
Dwg. Nr.: D95N-001  
Rev.: 03

Contents Subject to change without notice.