

**SPECIFICATION SHEET FOR EXEECO IB BEVEL, IS SPUR AND IW WORM
GEAR VALVE OPERATORS SUITABLE FOR MARINISED DUTY**

For marinised duty, Exeeco gearboxes are grease filled with Renolit CL-X2 (old name: Lacerta CL2X), to give an operating temperature range of -40°C to +120°C and are totally sealed to IP68.

The gearbox input shafts and keys are stainless steel.

All fasteners are bright zinc plated.

Gearcases, baseplates and input housings are cast iron to BS1452 grade 250 or SG iron to BS2789 grade 420/12.

All gearboxes are finished with PE3 primer suitable for overcoating with most conventional paints, polyurethanes, epoxies and chlorinated rubber paints. Note that the primer alone is not sufficient for this duty. The gearboxes must be overcoated with a suitable paint system and bonded to a cathodic protection system before use.

For the IB bevel and IS spur ranges, this standard allows continuous submersible duty to a depth of 15 metres in sea water.

For the IW worm range, this standard allows submersible duty for up to 72 hours to a depth of 15 metres in sea water.

Note that some ancillary equipment, such as dial indicators, may not be suitable for this duty.

Standard warranty conditions apply.

ISSUE 10

J.E. 17.01.07

F:\Exeeco\GBOX\PUB\Environmental Specs\mariduty.doc