



MAX BORE SQ KEY			MAX BORE RECTANGULAR KEY		
STD	BORE	KEY	STD	BORE	KEY
BS4235	-	-	BS4235	203.0	50X28
BS46	-	-	BS46	7.625"	2'X1 3/8"
ANSI B17.1	7.375"	1.3/4"SQ	ANSI B17.1	7.625"	2'X1 1/2"

INPUT FLANGE DETAILS (RATIO 480 TO 900)						
ISO	FLANGE O/DIA.	SHAFT DIA.	RECESS DIA.	RECESS DEPTH	HOLE DETAILS (OFF CENTRES)	KEY DETAILS
F25	Ø300	Ø50.00-0.05	Ø200.10+0.10	5	8 HOLES Ø16.5 (Ø0.65")	14X9X55
F25	Ø11.81"	Ø1.969"-0.002"	Ø7.878"+0.004"	(0.20")	ON Ø254.0 (Ø10.00") P.C.	(0.55"X0.35"X2.17")
FA25	Ø300	Ø50.00-0.05	Ø152.30+0.17	5	8 HOLES Ø16.5 (Ø0.65")	14X9X55
FA25	Ø11.81"	Ø1.969"-0.002"	Ø5.996"+0.007"	(0.20")	ON Ø254.0 (Ø10.00") P.C.	(0.55"X0.35"X2.17")

BASEPLATE DETAILS (ALL RATIOS) (ALTERNATIVES AVAILABLE ON REQUEST)	
ISO	HOLE DETAILS (22.5° OFF CENTRES)
F35	8 HOLES M30X36 (1.42") DEEP ON Ø356.0 (Ø14.02") P.C.
FA35	8 HOLES 1"UNCX36 (1.42") DEEP ON Ø355.6 (Ø14.00") P.C.
ISO F40	8 HOLES M36X36 (1.42") DEEP ON Ø406.0 (Ø15.98") P.C.
FA40	8 HOLES 1.25"UNCX36 (1.42") DEEP ON Ø406.4 (Ø16.00") P.C.



MANUAL UNIT



MOTORISED UNIT

APPROX WEIGHT: 602.9 kg



IW/MOW115IS12 QUARTER TURN GEARBOX, 480/ 600/ 720/ 900:1 RATIOS
MANUAL F25/ FA25 INPUT: F35/ FA35/ F40/ FA40 BASEPLATE

DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOR UP TO DATE DETAILS VISIT www.rotork.com

DRAWING No	PUB/IW115IS12	Regina House Ring Road Bramley Leeds LS134ET United Kingdom
ISSUE	2	
DATE	15/01/2013	