



BASEPLATE DETAILS (ALL RATIOS) (ALTERNATIVES AVAILABLE ON REQUEST)	
HOLE DETAILS (22.5° OFF CENTRES)	
ISO F35	8 HOLES M30X36 (1.42") DEEP ON Ø356.00 (Ø14.02") P.C.
FA35	8 HOLES 1"UNCX36 (1.42") DEEP ON Ø355.60 (Ø14.00") P.C.
ISO F40	8 HOLES M36X36 (1.42") DEEP ON Ø406.00 (Ø15.98") P.C.
FA40	8 HOLES 1.25"UNCX36 (1.42") DEEP ON Ø406.40 (Ø16.00") P.C.

MAX BORE RECTANGULAR KEY		
STD	BORE	KEY
BS4235	270.0	63 X 32
BS46	10.00"	2.3/4" X 1.7/8"
ANSI B17.1	10.00"	2.1/2" X 1.3/4"

MAX BORE SQ KEY		
STD	BORE	KEY
BS4235	-	-
BS46	-	-
ANSI B17.1	9.375"	2.1/2" SQ

DSIR RATIO	COMBINED RATIOS IW11			
	360:1	540:1	720:1	960:1
	1:1	360:1	540:1	720:1
4.25:1	1530:1	2295:1	3060:1	4080:1

APPROX WEIGHT: 517.4 kg



IW11IR3 QUARTER TURN GEARBOX, 360/ 540/ 720/ 960:1
 DSIR (DUAL SPEED INPUT REDUCER) INPUT: F35/ FA35/ F40/ FA40 BASEPLATE
 DETAILS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

DRAWING No	PUB-IW11IR3DSIR
ISSUE	A
DATE	18/05/2012

Regina House
 Ring Road
 Bramley
 Leeds
 LS134ET
 United Kingdom

FOR UP TO DATE DETAILS VISIT www.rotork.com