



Soldo Wireless Capabilities

Hostile terrain, remote locations, extreme weather and wiring costs are common barriers to properly monitoring, managing and servicing field equipment.

Wireless communication can solve them all.

Soldo has designed a limit switch box for linking the process with the control room wirelessly.

Designed for installation in both safe atmosphere and hazardous areas and for use in multiple industries including oil & gas - from gas pipelines to crowded off-shore platforms, where weight is an issue.

The main advantage over traditional wired technology is the ability to access and report back extensive diagnostic information from remote locations where wired technology is expensive or not an option.

Benefits of using this device in oil & gas and power generation industries include the reduction of installation costs, lowering energy consumption and minimising downtime.

Long life battery technology provides up to 10 years maintenance free operation.

Available in either die cast aluminium or 316 stainless steel with different lid choices made from the same enclosure material. Options include lids with a large visual indicator or flat lids without any visual indication.

The Soldo wireless limit switch box achieves ATEX certification using the Intrinsically Safe (IS) protection method.

Limit Switch Box Features

- Twin shaft design, ensuring a complete sealed device: the shaft is split into two parts, each fitted and sealed into the body and covered for the best weather insulation even when the cover is open
- Enhanced corrosion resistance using thick polyester powder coating on aluminum housings
- 316 stainless steel housing for maximum protection in hostile and corrosive environments
- Easy wiring through the terminal PCB board
- Captive bolts on the screwed lid



Wireless Communication Features

- 10 years average battery life
- Full range position feedback
- Diagnostic reporting for predictive maintenance
- Wireless adaptor for field process switches including: pressure, level and other digital feedbacks
- Connection to Rotork Pakscan™ wireless network

Linking the Process
with the Control Room



www.soldo.net

Europe

Soldo SRL
Via Monte Baldo, 60
25015 Desenzano Del Garda
Brescia, Italy

Tel: +39 030 9991309
Fax: +39 030 9141977
Email: sales@soldo.net

USA

Soldo USA LLC
3920 Westpoint Blvd.
Winston-Salem
NC 27103

Tel: +1 (336) 659 3400
Fax: +1 (336) 659 9323
Email: sales@soldousa.com

PUB109-012-00
Issue Date 11/14

As part of a process of on-going product development, Soldo reserves the right to amend and change specifications without prior notice. Published data may be subject to change. For the very latest version release, visit our website at www.soldo.net

The name Soldo® is a registered trademark. Soldo recognizes all registered trademarks.
Published and produced in the UK by Soldo. POWTG114

