



NOTES: 1) ALL DIMENSIONS ARE IN mm WITH CONVERSION FOR (INCHES).
 2) CMA ACTUATORS CAN BE SELECTED WITH EITHER METRIC OR IMPERIAL SIZES FOR MOUNTING, SHAFT AND CONDUIT ENTRY. THESE ARE NOT SIMPLE CONVERSIONS BUT DIFFERENT DIMENSIONS.

DIMENSIONS WITH ' * ' INDICATE COVER REMOVAL ALLOWANCE.

THE INTERFACE PROVIDED FOR MOUNTING THE ACTUATOR ON TO THE VALVE SHOULD CONFORM TO GOOD ENGINEERING PRACTICES, ENSURING ADEQUATE TOLERANCES, THREAD ENGAGEMENT, SCREW TORQUES, SIZES, MATERIALS & FORM TOLERANCES.

UNIT WEIGHT - 18.4 lbs (8.3 Kg)

TOLERANCES			rotork® Process Controls MILWAUKEE, WISCONSIN, USA	TITLE: CMA INSTALLATION DRAWING	
DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED				FOR: CML-100 CML-250	96
X = ±.5mm .XX = ±.1mm ANGULAR ±1°					
SCALE: 1:2			This print is the property of Rotork Process Controls and is loaned in confidence subject to return. All rights to design or invention are reserved.	047523	
DRAWN: SSV	PROD. DV. RLY	PROD. ENG. RLY			
DATE: 5/27/15	DATE:	DATE: 09/20/12			