



REV.NO.	REVISION DESCRIPTION	DRAWN / DATE	REVIEWED / DATE	APPROVED / DATE
	Previous versions omitted			
△	To remote sensor ...	KCH/20241105	JCS/20241105	KTJ/20241105
△	Drawing updated	KCH/20250108	JCS/20250108	KTJ/20250108

Specifications

Motion Type	Linear	
Housing Material	Aluminum	
Acting Type	<input type="checkbox"/> Single <input type="checkbox"/> Double	
Input Signal	4-20 mA DC	
Minimum Current Signal	3.8 mA	
Noise Range	50 mVp.p	
Supply Pressure	0.14 to 0.7 MPa (1.4 to 7 bar, 20 to 102 psi)	
Stroke	10 to 150 mm (0.4" to 6")	
Lever Type	<input type="checkbox"/> 10 to 40mm <input type="checkbox"/> 70 to 70mm <input type="checkbox"/> 50 to 100mm <input type="checkbox"/> 100 to 150mm	
Cable length	<input type="checkbox"/> 5 m <input type="checkbox"/> 10 m <input type="checkbox"/> 15 m <input type="checkbox"/> 20 m	
Impedance	Max. 500 Ohm @ 20 mA DC	
Conduit entry, Air Connection	<input type="checkbox"/> G 1/2, Rc 1/4 <input type="checkbox"/> G 1/2, 1/4 NPT <input type="checkbox"/> G 1/2, 1/4 NPT <input type="checkbox"/> M20x1.5P, 1/4 NPT <input type="checkbox"/> 1/2 NPT, 1/4 NPT	
Gauge Connection	1/8 NPT	
Explosion Protection	Non-Explosion proof	
Operating Temp.	Positioner	
	<input type="checkbox"/> Standard : -30 to 85 °C (-22 to 185 °F)	
	<input type="checkbox"/> Low temp. : -40 to 85 °C (-40 to 185 °F)	
Sensor	<input type="checkbox"/> Arctic temp. : -55 to 85 °C (-67 to 185 °F) (only Non-Explosion)	
Linearity	± 0.5 % F.S.	
Hysteresis	± 0.5 % F.S.	
Sensitivity	± 0.2 % F.S.	
Repeatability	± 0.3 % F.S.	
Air consumption	Below 2 LPM (Sup. = 0.14 MPa, 1.4 bar)	
Flow Capacity	70 LPM (Sup. = 0.14 MPa, 1.4 bar)	
Ingress Protection	IP66 (excluding the pressure gauges)	
Output Characteristics	Linear, EQ%, Quick Open, User set	
Vibration	No Resonance up to 100 Hz @ 6 G	
Humidity	5 to 95 % RH @ 40 °C	
Main Board	MPU	16 bit Micro Controller
	A/D Converter	12 bit
	D/A Converter	12 bit
Communication	HART Communication (HART 7)	
Analog Output	<input type="checkbox"/> None <input type="checkbox"/> 4-20 mA (DC 9 to 28 V)	
	Positioner	2.5 kg (5.5 lb)
Weight	Sensor	0.6 kg (1.2 lb)
	Cable (5 m)	0.6 kg (1.3 lb)

No.	PART NAME	MATERIAL	Q'ty	REMARK
1	Base cover	ALDC12	1	Positioner
2	Base body	ALDC12	1	
3	Pressure gauge	STS304	1 or 2	
4	Junction box	ALDC12	1	
5	Vent cover	PC	1	
6	Base body	ALDC12	1	Remote sensor
7	Base cover	ALDC12	1	
8	Feedback lever	STS304	1	
9	Cable gland	-	2	
10	Cable	-	1	

NOTE
1. Conduit M20x1.5P and 1/2 NPT are adapter type.

SURFACE TEXTURE		PRODUCT NAME		rotork Rotork YTC Limited GMP0-SI, KOREA
FINISH TREATMENT		Smart positioner		
MATERIAL		MODEL	SCALE	TITLE Linear, Standard
OTHERWISE NOTE		3rd	1 / 3	
GENERAL TOLERANCE		PROJECTION	SHEET No.	DRAWING NO.
		1	1 / 1	YTC-3702L-1
		QUANTITY		REV.
		1		3